CLEANING, SEALING & AFTERCARE

COLOUR INTENSIFIER AND STAINBLOCK IMPREGNATING SEALER
TECHNICAL DATA SHEET

REF: LTP/13

LTP Colour Intensifier & Stainblock

Impregnating Sealer

For interior and exterior use.
For all types of natural and artificial stone, unglazed porcelain, sandstone, slate, marble, terracotta, quarry, brick and concrete.
Provides enhanced matt finish. For use on wall and floor surfaces. Strongly protects against water, oil grease and dirt. Allows surface to breathe.

Directions for use

For application and cleaning tools see LTP website.

This Impregnating sealer is very difficult to remove once hardened. Do not over apply. The surface to be treated must be completely clean, dry and free from contamination.
If necessary, first clean floor with LTP Grimex and allow to dry thoroughly. Apply thinly and uniformly with a cloth, brush, sealant applicator pad or sponge and leave for 15-30 minutes before wiping over with a clean dry fluff-free cloth to remove all and any excess. **N.B.** The surface must retain a natural finish after treatment. Any excess left on the surface could oxidise to form an unsightly gloss varnish. For stronger colour enhancement and in the case of more absorbent surfaces, further coats may be applied. Allow at least 30-60 minutes before applying further coat. This product will dry after about two hours, but will take a further three days to become fully resistant. Do not apply in direct sunlight or in a temperature exceeding 25°C. **Use only in well-ventilated areas.** Do not apply on floors with under floor heating on as the product may dry prematurely.

FOLLOWING APPLICATION DO NOT ALLOW SURFACES TO GET WET AND KEEP DRY FOR A MINIMUM OF 3 DAYS. Always test first on an inconspicuous area, prior to general application.

Coverage

Per $10m^2$
Lower porosity floor: approximately 1-2 litres
Higher porosity floor: approximately 3-4 litres

Aftercare

Routinely sweep the floor and wash with LTP Waxwash. Clean walls and work surfaces with LTP Stonewash spray.

Storage information

Store in a cool, dry, frost-free environment. Shelf Life – Up to 4 years for un-opened containers.

Health, Safety & Environmental

Contains: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics, Kerosine (petroleum), hydrodesulfurized, Hydrocarbons, C9, aromatics, n-butyl acetate.

Flammable liquid and vapour. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects.
Keep out of the reach of children. If medical advice is needed, have product container or label at hand. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing vapours, spray. Use only outdoors or in a well-ventilated area. IF SWALLOWED: Immediately call a POISON CENTER, a doctor. Do NOT induce vomiting. Store locked up. Dispose of contents and container to a hazardous or special waste collection point. Repeated exposure may cause skin dryness or cracking.
UFI: 94A0-M03G-R00Y-FYFS
UN: 1300



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.

For any LTP product information call our technical helpline
+ 44 (0) 1823 666213| www.ltp-online.co.uk| technical@ltp-online.co.uk
Tone Est, Milverton Road, Wellington, Somerset, TA21 0AN