CLEANING, SEALING & AFTERCARE

MPG –POLISHED MARBLE, PORCELAIN & GRANITE SEALER TECHNICAL DATA SHEET

REF: LTP/21

LTP MPG SEALER

Impregnating Sealer

For interior use

MPG: for polished marble, porcelain, granite & encaustics.

Colourless impregnating sealer. Suitable for polished floors, walls, worktops and fireplaces. Does not alter the polished finish of the surface.

Directions for use

For application and cleaning tools see LTP website.

Surfaces should be completely clean and dry. If necessary use LTP Grimex. NB: It is important to remove any factory applied sealer or wax from the tiles before sealing. Apply thinly and uniformly using a soft cloth, sealant applicator pad or sponge. Within 20 minutes, whilst the sealer is still wet on the surface, buff well using a clean dry cloth or buffing machine. Leave to dry for 4 hours and then on more porous surfaces apply a second coat using the same method. It is important to remember to remove any excess from the surface and buff well between each coat. Do not apply in temperatures exceeding 25°C. Ensure underfloor heating is switched off. Over applied sealer will dry leaving a greasy residue on the surface. To remove, apply white spirit or a little more sealer and then buff immediately. Always test on an inconspicuous area first. Treated areas should be dry enough to walk on after about 4 hours but will take 3 days to become fully resistant.

Use only in well ventilated areas. Do not breathe vapours.

Coverage

Approximately 10 - 30 square metres/litre depending on surface porosity.

Aftercare

Use LTP Porcelain Floor Tile Cleaner and LTP Stonewash for walls. For stubborn surface marks use LTP Grimex, in which case you may need to re-seal treated areas. Do not use strong bleach cleaners for routine aftercare.

Storage information

Store in a cool, dry, frost-free environment.
Shelf Life – Up to 4 years for un-opened containers.

Health, Safety & Environmental

Contains: Contains Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics, n-butyl acetate
Flammable liquid and vapour. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness.
Keep out of the reach of children. If medical advice is needed, have product container or label at hand. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing spray, vapours. Avoid breathing spray, vapours. Use only outdoors or in a well-ventilated area. IF SWALLOWED: Immediately call a doctor, a POISON CENTER. Do NOT induce vomiting. Store locked up. Dispose of contents and container to a hazardous or special waste collection point. Repeated exposure may cause skin dryness or cracking.
UFI: E1A0-30E3-F00G-TMVQ
UN: 1300

DANGER



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.

2025

For any LTP product information call our technical helpline
+ 44 (0) 1823 666213| www.ltp-online.co.uk| technical@ltp-online.co.uk
Tone Est, Milverton Road, Wellington, Somerset, TA21 0AN