



# CLEANING ■ SEALING ■ MAINTENANCE

Sealing and maintenance solutions for all types of stone, porcelain, quarry, terracotta and glazed ceramic

## COLOUR INTENSIFIER TECHNICAL DATA SHEET REF: 13/5/1/5

### LTP Colour Intensifier & Stainblock

#### Colour Enhancing Tile Sealer

##### For interior and exterior use.

Suitable for slate, natural stone, tumbled marble, travertine, terracotta, quarry, terrazzo and sandstone. Provides enhanced matt finish. For use on wall and floor surfaces. Strongly protects against water, oil, grease and dirt. Allows surface to breathe.

### Directions for use

This sealer is very difficult to remove once hardened. Do not over apply. The surface to be treated must be completely clean, dry and free from contamination. If necessary, first clean floor with LTP Grimex and allow to dry thoroughly. Apply this sealer thinly and uniformly with a cloth, brush or sponge and allow to penetrate for approximately 15-30 minutes before wiping over with a clean dry fluff-free cloth to remove all and any excess which may remain on the surface. **N.B.** The surface must retain a natural finish after treatment. Any excess left on the surface could oxidise to form an unsightly gloss varnish. For stronger colour enhancement and in the case of more absorbent surfaces, further coats may be applied. Allow at least 30-60 minutes from application of previous coat before applying further coat. This product will dry after about two hours, but will take a further three days to become fully resistant. Do not apply in direct sunlight or in a temperature exceeding 25°C. Use only in well-ventilated areas. Beware of application upon floors with under floor heating as the product may dry prematurely. If you are unsure of correct application methods, test on an inconspicuous area, prior to general application. **Use only in well ventilated areas. Do not breathe vapours.**

### Coverage

Per 10m<sup>2</sup>  
Lower porosity floor: approximately 1-2 litres  
Higher porosity floor: approximately 3-4 litres

### Maintenance

Routinely sweep the floor and wash with LTP Waxwash. Clean walls and work surfaces with LTP Stonewash spray. For further information, refer to the technical data sheet.

### Storage information

Store in a cool, dry, frost-free environment.  
Shelf Life – Up to 4 years for un-opened containers.

This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.

*for beautiful surfaces we have the solutions...*

LTP, Tone Estate, Milverton Road, Wellington, Somerset, TA21 0AN  
T +44 (0) 1823 666213 F +44 (0) 1823 665685 E info@ltp-online.co.uk  
[www.ltp-online.co.uk](http://www.ltp-online.co.uk) January 2013

### Health & Safety

**Contains: White Spirit (naphtha (petroleum), hydrodesulphurised heavy (<0.1% benzene)).  
Flammable liquid and vapour. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects.**

Store locked up. Keep out of reach of children.  
Avoid release to the environment. Keep away from open flames-No smoking. Wear protective gloves.  
IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
Get medical advice/attention. Dispose of contents/ container to hazardous waste collection point.



Danger

### VOC STATEMENT

EU limit value for this product (Cat A/h) 750g/L (2010).  
This product contains max 749g/L VOC.

### UN 1300

EC Label. EC No 1272/2008.

