## NO MORE PLY MEGA STRENGTH ADHESIVE

#### 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: NO MORE PLY MEGA STRENGTH ADHESIVE

Product code: 5620

Use / description of product: Harmful. Irritant. Sensitising.

Company name: SPECIALIST TILING SUPPLIES

**UNIT 5 WORTLEY MOOR TRADING ESTATE** 

WORTLEY MOOR LANE

LEEDS, WEST YORKSHIRE

LS12 4HX ENGLAND

Tel: 0044 113 2022 010 Fax: 0044 113 2022 015

#### 2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: DIPHENYLMETHANE DIISOCYANATE (ISOMERS AND HOMOLOGUES) 10-30%

CAS: 9016-87-9

[Xn] R20; [Xi] R36/37/38; [Sens.] R42

## 3. HAZARDS IDENTIFICATION

Main hazards: Harmful by inhalation. Irritating to eyes, respiratory system and skin. May

cause sensitisation by inhalation.

#### 4. FIRST AID MEASURES (SYMPTOMS)

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and

stomach pain may occur. There may be vomiting.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

# 4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to

skin. Drench the affected skin with running water for 10 minutes or longer if

substance is still on skin. Consult a doctor.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a

litre of water to drink immediately. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so.

Consult a doctor.

## NO MORE PLY MEGA STRENGTH ADHESIVE

#### 5. FIRE-FIGHTING MEASURES

Extinguishing media: Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water

spray to cool containers.

**Exposure hazards:** In combustion emits toxic fumes.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent

contact with skin and eyes.

#### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions: If outside do not approach from downwind. If outside keep bystanders upwind

and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up

to prevent the escape of liquid.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Clean up should be dealt with only by qualified personnel familiar with the

specific substance. Allow product to solidify and remove it by mechanical means. Remove uncured foam with acetone Transfer to a closable, labelled

salvage container for disposal by an appropriate method.

## 7. HANDLING AND STORAGE

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation

of the area. Do not handle in a confined space. Avoid the formation or spread

of mists in the air.

Storage conditions: Store in cool, well-ventilated area. Keep container tightly closed. Store in

original containers between +5 and +25°C. Storage outside these paramaters

will dramatically reduce shelf life and invalidates all product warrenties.

Suitable packaging: Must only be kept in original packaging.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: DIPHENYLMETHANE DIISOCYANATE (ISOMERS AND HOMOLOGUES)

TWA (8 hr exposure limit): 0.02 mg/m3 STEL (15 min exposure limit): 0.07

mg/m3 (OES)

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

Gas/vapour filter, type A: organic vapours (EN141). must be worn if vapour

concentration is above OES or if ventilation is poor

Hand protection: Impermeable gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

## NO MORE PLY MEGA STRENGTH ADHESIVE

**Skin protection:** Impermeable protective clothing.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

State: Paste

Colour: Colourless

**Odour:** Barely perceptible odour

**Evaporation rate:** Negligible **Solubility in water:** Insoluble

Also soluble in: Most organic solvents in uncured state.

Viscosity: Highly viscous

Viscosity value: 300000mpas

Boiling point/range°C: 200

Flash point°C: not applicc.

Autoflammability°C: >200

Relative density: 1.03

#### 10. STABILITY AND REACTIVITY

**Stability:** Stable under normal conditions. Stable at room temperature.

**Conditions to avoid:** Heat. Moist air. Humidity. Direct sunlight.

Materials to avoid: Strong oxidising agents. Strong acids.

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide. In

combustion emits toxic fumes of hydrogen cyanide.

#### 11. TOXICOLOGICAL INFORMATION

Hazardous ingredients: DIPHENYLMETHANE DIISOCYANATE (ISOMERS AND HOMOLOGUES)

ORL RAT LD50 49 gm/kg SKN RBT LD50 >9400 mg/kg

**Chronic toxicity:** May cause sensitisation by inhalation. May cause sensitisation by skin contact.

**Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

# 12. ECOLOGICAL INFORMATION

Persistence and degradability: No data available.

**Bioaccumulative potential:** No data available.

Other adverse effects: Negligible ecotoxicity. Not dangerous to ozone layer (1999/45/EC)

## NO MORE PLY MEGA STRENGTH ADHESIVE

#### 13. DISPOSAL CONSIDERATIONS

Disposal operations: Waste material code (91/689/EEC, Council Decision 2001/118/EC, O.J L47 of

16/2/2002):

**Disposal of packaging:** 08 05 01 (waste isocyanates)

Waste material code packaging (91/689/EEC); Council decision 2001/118/EC,

O.J L47 of 16/2/2001) 15 01 10 (packaging containing residues of or

contaminated by dangerous substances)

**NB:** The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

## 14. TRANSPORT INFORMATION

ADR / RID

UN no: -

Shipping name: "NOT SUBJECT TO ADR"

IMDG / IMO

UN no: -

IATA / ICAO

UN no:

# 15. REGULATORY INFORMATION

Hazard symbols: Harmful.

**Risk phrases:** R20: Harmful by inhalation.

R36/37/38: Irritating to eyes, respiratory system and skin.

R42: May cause sensitisation by inhalation.

**Safety phrases:** S2: Keep out of the reach of children.

S13: Keep away from food, drink and animal feeding stuffs.

S23: Do not breathe vapour.

S37/39: Wear suitable gloves and eye / face protection.

S45: In case of accident or if you feel unwell, seek medical advice immediately

(show the label where possible).

S63: In case of accident by inhalation, remove casualty to fresh air and keep at

rest.

**Precautionary phrases:** Contains isocyanates. See information supplied by the manufacturer.

# NO MORE PLY MEGA STRENGTH ADHESIVE

**Note:** The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

# 16. OTHER INFORMATION

**Risk phrases used in s.2:** R20: Harmful by inhalation.

R36/37/38: Irritating to eyes, respiratory system and skin.

R42: May cause sensitisation by inhalation.

Legal disclaimer: The above information is believed to be correct but does not purport to be all

inclusive and shall be used only as a guide. This company shall not be held

liable for any damage resulting from handling or from contact with the above

product.